

	<h1>Technical Bulletin</h1>	Flying Pig Systems	Page 1/2
	<h2>Road Hog Bios Settings</h2>	Rev. Date 23-Nov-09	Rev A

This document contains instructions for configuring the bios settings for your Road Hog console. You can identify the motherboard model of your Road Hog during boot-up or by contacting support.

---

## Accessing the Bios

- 1) Attach a keyboard to the console and power on the console.
  - 2) During the boot process, press and hold the DELETE key
  - 3) The BIOS Setup Utility will open.
  - 4) Follow the guidelines below to restore the default Road Hog settings per motherboard model.
- 

### (AIMB-562)

The following changes need to be made to each section of the BIOS in the Road Hog computer when using an AIMB-562 motherboard. After making the changes, press F10 to save the configuration and exit.

#### MAIN

- > Adjust System time and date
- > Legacy Diskette A: Disabled

#### ADVANCED

##### **Chipset**

- > Graphics Adapter Priority: PCI Express/Int-VGA

##### **Onboard Devices Configuration**

- > HD Audio Controller: Disabled
- > Onboard PCIEX GbE LAN: Disabled
- > Serial Port1 Address: Disabled
- > Serial Port2 Address: Disabled
- > Parallel Port Address: Disabled

#### POWER

- > ACPI 2.0 Support: Yes

##### **APM Configuration**

- > Restore on AC Power Loss: Power On

##### **Hardware Monitor**

- > CPU Fan
- Profile Mode: Silent Mode

#### BOOT

##### **Boot Device Priority**

- > 1st boot: Hard Drive
- > 2nd boot: Removable Device
- > 3rd boot: USB CD-ROM

##### **Boot Settings Configuration**

- > Quick boot: Enabled
- > Full Screen Logo: Disabled
- > Wait for 'F1' if error: Disabled

	<b>Technical Bulletin</b>	Flying Pig Systems	Page 2/2
	<b>Road Hog Bios Settings</b>	Rev. Date 23-Nov-09	Rev A

## (ASUS P5B)

The following changes need to be made to each section of the BIOS in the Road Hog computer when using an Asus P5B motherboard. After making the changes, press F10 to save the configuration and exit.

### MAIN

- > Adjust System time and date
- > Legacy Diskette A: Disabled

### ADVANCED

#### **Chipset**

##### **Northbridge Configuration**

- > Initiate Graphics Adapter: PCI/IGD

##### **Onboard Devices Configuration**

- > HD Audio Controller: Disabled
- > Onboard 1394 Controller: Disabled
- > Onboard PCIE GbE LAN: Disabled
- > JMicron SATA/PATA Controller: Enabled
- > Serial Port1 Address: Disabled
- > Parallel Port Address: Disabled

### POWER

- > ACPI 2.0 Support: Enabled

#### **APM Configuration**

- > Restore on AC Power Loss: Power On
- > Power On By PCI Devices: Disabled
- > Power on By PCIE Devices: Disabled
- > Power on By PS/2 Keyboard: Disabled

#### **Hardware Monitor**

- > Fan Profile: Silent

### BOOT

#### **Boot Device Priority**

- > 1st boot: CD-ROM
- > 2nd boot: Hard Drive

#### **Boot Settings Configuration**

- > Quick boot: Enabled
- > Full Screen Logo: Enabled
- > Wait for 'F1' if error: Disabled